



**POWERTRAIN**

Cat® C3.4 Tier 4 engine, 74 hp (55 kW) (No DEF)  
2-Speed hydrostatic drive  
250 fpm (76 mpm) max transport speed  
Automatic track tensioning  
70" (1778 mm) track length  
53" (1346 mm) of ground contact  
12" (305 mm) steel track pads standard  
14" (356 mm) performance, poly track pads option  
5 track rollers per side  
125mm track chain pitch  
Hydraulically driven 12 kW generator w/ GFCI breakers  
Variable speed hydraulically driven fan

**OPERATING ENVIRONMENT**

Dual side operation  
LCD display provides conditions and diagnostics  
Manual ground drive controls  
Push button keypads  
Pause mode enables return to same settings

**MATERIAL DELIVERY**

7-ton (6.35 mt) hopper  
Replaceable floor plates  
Heavy-duty chains and flight bars  
Direct drive conveyor headshaft  
Reversible conveyor  
Flow gate style cutoff door  
Adjustable push roller  
Independent auger and conveyor controls  
Independent hopper controls

**SCREED**

7'8" (2.3 m) to 14'4" (4.4 m) standard paving width  
Screed mounted upper and lower 9" (228 mm) augers  
Electric heated screed with 4 elements  
Patented endgate design  
3/8" (9.5 mm) thick, replaceable screed plates  
2,500 vpm vibrator

**MAINTENANCE/SERVICE**

8-gal (30 L) spray down system with 4 hoses/nozzles  
Braided electrical harnesses and sealed connections  
Color-coded electrical wires  
12-volt electrical system with automotive-type fuses  
Remote grease fittings  
5 engine access doors  
Lockable vandal cover and engine access doors



**OPTIONAL EQUIPMENT**

14" (356 mm) Poly Track Pads  
LED Strobe Light  
Lighting Group (4 Lights)  
Premium Lighting Group (8 LED Lights)  
Sonic Controlled Augers  
Heated End Gates

**WARRANTY**

12 months standard  
Extended warranty available

**SALES AND SERVICE**

Sold and serviced exclusively through Cat dealers worldwide

**SPECS**

Weight (including screed):	16,200 lb	7,348 kg
Length:	12' 7"	3,835 mm
Width:	98"	2,489 mm
Height:	70"	1,778 mm
Truck Clearance:	18"	457 mm
Auger Diameter:	9"	228 mm
Auger Speed:	110 rpm	
Fuel Tank Capacity:	26 gal	98 L
Hydraulic Tank Capacity:	30 gal	113 L
Transport Speed:	250 fpm	76 mpm
Max Paving Speed:	150 fpm	45 mpm
Screed Weight:	3,000 lb	1,360 kg
Main Screed Plate Width:	16.5"	419 mm
Screed Extension Plate Size:	9"	228 mm
Vibration:	1 x 2,500 vpm	



## SIMPLIFIED OPERATION

- Mechanical controls provide reliable operation
- Cable operated ground drive controls allows operation from either side of the machine
- Push button keypads for feeder system, engine rpm and ground speed
- Flow gate style cutoff door manages head of material
- 4 spray down coiled hoses operate on timed pump



## DURABLE COMPONENTS

- Highway class chains, slats and idler bearings
- Proven Cat® C3.4B T4 engine with 74 hp (55 kW) and no DEF requirement
- Operating weight of 16,200 lb (7,348 kg)
- Low profile undercarriage
- Planetary drive with integrated 2-speed hydraulic motor and park brake
- 125mm track with 12" (305 mm) steel pads standard
- 14" (356 mm) poly pad option
- Direct-drive conveyor headshaft eliminates drive chain



## INNOVATIVE SCREED

- 7'8" (2.3 m) to 14'4" (4.4 m) standard paving width
- Screed mounted 9" (228 mm) augers help distribute mix across the screed
- Electric screed heats at low engine rpm
- Sonic controlled auger option manages head of material
- Extension angle of attack adjustment located at endgate for quick adjustments
- Patented endgate design features one crank for height and one crank for angle while the rear edge stays at the same height



## EXCELLENT VISIBILITY AND CONTROL

- Lower hood design increases operator visibility into the hopper
- Controls are grouped and within easy reach of the operators
- Height adjustment cranks angled for comfort and convenience
- Dual side operation
- Push button keypads for feeder system, engine and ground speed
- Electronic controller provides diagnostic capability
- Folding walkway allows smaller starting pad in tight locations



## SERVICE AND SUPPORT

- Cat® Dealer sales, service and support
- Remote grease lines for simplified daily maintenance
- Visual indicators for routine maintenance checks
- Weiler trained dealer service technicians
- Product and application assistance from certified paving specialists
- Readily available, off-the-shelf OEM parts that meet precise specifications