

E650C WINDROW ELEVATOR



BUILT FOR HIGH PRODUCTION.

High-slat entry tackles tall windrows with 60" (1524 mm) wide conveyor throat and 600 tph (544 mtph) capacity. 3-point suspension and adjustable scrapers ensure a clean path for the elevator and paver.



RELIABLE POWER.

The Cat® C4.4 Tier 4F engine with 137 HP (102 kW) produces clean, quiet power. The elevator is powered by a high-torque, direct-drive motor which eliminates a gearbox and is kept cool by a loop flush return system.



SIMPLE CONTROLS.

Operating controls are located on both sides of the machine with easy-to-access chain speed and direction control. Variable hydraulic drive system allows the speed of the elevator to match material and production requirements.



REMIXING DISCHARGE HOPPER.

The optional remixing discharge hopper provides consistent material mix to the paver with independent doors to control material flow and hydraulically moves into and out of position.



TRANSPORT AXLE.

The optional transport axle simplifies transportation of the E650C or E550C windrow elevator at highway speeds. The axle quickly pins on and off the elevator and includes a hydraulic tongue for convenient hook-up to the tow vehicle.



FAST SERVICE.

Two large doors and platforms allow easy access to the engine compartment. Electronic controller provides machine conditions, diagnostics and calibrations. Caterpillar dealer service, support and inventoried parts help keep the machine up and running.



E550C SPECIFICATIONS

WEIGHT	21,680 lb	9843 kg	ENGINE	Cat® C4.4 Tier 4F	DISCHARGE HEIGHT	84"	2134 mm	
HEIGHT	124"	3150 mm	HORSEPOWER	137 hp	102 kW	FRONT WHEEL CYL. LIFT	8"	203 mm
LENGTH	230"	5842 mm	THROAT WIDTH	60"	1524 mm	FRONT TIRE SIZE	22" (559 mm) x 7" (178 mm)	
LENGTH (RAISED TOW)	188"	4775 mm	ELEVATOR SLAT WIDTH	58"	1473 mm	REAR TIRE SIZE	235/75/17.5	
WIDTH (WINGS IN)	122"	3099 mm	ELEVATOR SLAT DEPTH	7"	178 mm	FUEL CAPACITY	80 gal	303 L
WIDTH (WINGS OUT)	184"	4674 mm	AUGER DIAMETER	29"	737 mm	HYDRAULIC CAPACITY	40 gal	151 L

POWERTRAIN

- Cat® C4.4 Tier 4F engine
- 137 hp (102 kW)
- High-torque, direct drive motor powers elevator

OPERATING ENVIRONMENT

- Dual side operating controls
- Adjustable speed chain control with reverse
- Variable speed drive system

MATERIAL DELIVERY

- 600 tph (544 mtph) capacity
- 3-point suspension system
- 118" (2997 mm) elevator throat width
- 29" (737 mm) converging augers
- 84" (2134 mm) discharge height
- 58" (1473 mm) wide by 7" (178 mm) deep elevator slats
- 8" (203 mm) front wheel cylinder lift
- Three independent adjustable scrapers

PAVER HOOKUP

- Toolless sliding hitch
- Swing-up towing frame
- Hydraulic pin push frame option

OPTIONAL REMIXING DISCHARGE HOPPER

- Provides consistent mix of material to paver
- Hydraulically moves into and out of position

SALES AND SERVICE

Sold and serviced through Caterpillar dealers worldwide.

OPTIONAL TRANSPORT AXLE

- Heavy-duty 22,500 lb (10 205 kg) axle
- Tow elevator at highway speeds
- Hydraulic lift cylinders
- Hydraulic towing frame
- Quickly pins on/off elevator

SERVICE/MAINTENANCE

- Hinged engine doors accessible from large platforms
- Greaseless, phenolic pads
- Electronic controller provides machine diagnostics and calibrations
- Face-sealed hoses and fittings
- Braided electrical harnesses and sealed connections
- Color-coded and numbered electrical wires

OPTIONAL EQUIPMENT

- Transport axle
- Hydraulic tongue
- Hydraulic pin push frame
- Remixing discharge hopper
- Chromium carbide floor plates
- Spray down for chains and sprockets
- LED lights

WARRANTY

12 months standard. Extended warranty available.